
This drawing, specifications, and concepts contained herein are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS							
	REV	DESCRIPTION	DATE	INITIAL	APPROVED		
	1	CH'D TITLEBLOCK & REVISION BLOCK, ADDED ENGRAVE NOTE -1, CH'D ASSY. VIEW TO -A WELDMENT & ADDED TO BOM. CH'D -1 I.D. FROM 2.780 TO 2.787±.002 TO ACCOMMODATE BOTH STEEL & ALUMINUM CLUTCH KNURLED NUTS PER D.W., DELETED -9 FROM BOM.	1/15/10	RJC	RW		
	2	DELETED -A, -3, & -5, CH'D -7 TO -2, CH'D -1 FROM RING TO WRENCH. CH'D -1 WRENCH TO ONE PIECE DESIGN PER D.W.	3/16/12	RJC	RW		



RED BARN MACHINE

TITLE OVERRUNNING CLUTCH WRENCH REV

DWG NO. RBT18618 UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON
DECIMALS
.XXX ± .005 FRACTIONS ± 1/32 DRAWN BY:

DATE

.XX ± .01 .X ± .1

NTS

SCALE

COLE APPROVED D Weil FRACTIONS ± 1/32 ANGLES ±.5° UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES

0.15 × 45* PR .015 R


2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL MD 500 C MD 500 D

1 of

3-25-02 SHEET

ASS QT	YASSY (QTY	B/0	PART	# QTY	DESCRIPTION	MATERIAL	B/O INFORMATION OR SPECIFICATIONS
	1		-1	1	WRENCH	1018	1/2 × 4-1/2 × 6-7/8
		B/0	-2		HANDLE		CAST IRON W/STUD (REID #KA-3 OR EQUIV.)
	ASS/	1					

REVISIONS							
REV	DESCRIPTION	DATE	INITIAL	APPROVED			
1	CH'D TITLEBLOCK & REVISION BLOCK, ADDED ENGRAVE NOTE -1, CH'D ASSY. VIEW TO -A WELDMENT & ADDED TO BOM. CH'D -1 I.D. FROM 2.780 TO 2.787±.002 TO ACCOMMODATE BOTH STEEL & ALUMINUM CLUTCH KNURLED NUTS PER D.W., DELETED -9 FROM BOM.	1/15/10	RJC	RW			
2	CH'D -1 WRENCH TO ONE PIECE DESIGN PER D.W.	3/16/12	RJC	RW			



® RED BARN MACHINE TITLE OVERRUNNING CLUTCH WRENCH DWG NO. RBT18618-1 UNLESS DTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES DN: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ±.5* COLE APPROVED D Weil FRACTIONS ± 1/32 BLACK DXIDE UNLESS DTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES 0.15 × 45° PR 0.15 2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL MD 500 C MD 500 D DATE 3-25-02 SHEET 2 of 2 NTS

REVISIONS DESCRIPTION APPROVED DATE

NOTE: NORMALIZE RING, MILL FLAT, WELD EARS, MILL SLOT & RELIEF.

KNURLED NUT DUTSIDE DIAMETER Ø2.787 STEEL Ø2.775 ALUMINUM 27 FEB 2002

This drawing, specifications, and concepts contained herein are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

PART #	QTY	DESCRIPTION
-1	1	RING - 1018 Ø4 1/2 DD x Ø2 3/4 ID X 9/16
-3	1	LEG - 1018 1/2 x 3/4 X 2 1/2
-5	1	LEG - 1018 1/2 x 3/4 X 2 1/2
-7	1	HANDLE - CAST IRON, WITH STUD (REID #KA-3 OR EQUIV.)

FOR OPTIONAL SPREADER AS SOLD TO HELI-CRAFT REFER TO MASTER PRINT

PART #	QTY	DESCRIPTION			
		REQUIRED FOR OPTIONAL SPREADER ONLY			
-9	1	HAND KNOB - 1/4-20 STUD x 1 1/2 (REID #KA-202 OR EQUIV.)			

	DRAWN BY: CDLE	_
	CHECKED	1R
	HEAT TREAT	[13
	SPEC BLACK DXIDE	TITLE
USED ON MODEL	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	'
MD 500 C	TOLERANCES ON:	Ш
MD 500 D	.XXX ± .010	DWG
	<u>'X^ ± 13 ± 13 </u>	
	UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES	
	.015 × 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	SCAL
	LI DANESTOLINE CATALO HITEL HITEK I EHILING	

RED BARN MACHINE

OVERRUNNING CLUTCH WRENCH

RBT18618

ALE NTS DATE 3-25-02 SHEET 1 of 1